



FLEXSTONE COLORCOAT AR
FOR USE ON TEXTURED STONE SYSTEM

PRODUCT DESCRIPTION

COMPOSITION: COLORCOAT AR is a single component, liquid applied, moisture-cured, aromatic, polyurethane surface protection coating.

BASIC USES: COLORCOAT AR is the low cost wear surface topcoat used in the FLEXSTONE Decking Systems. COLORCOAT AR is the "aggregate receiving coat" in the decorative textured stone decking system.

PACKING: Available in 5 gallon containers.

PRE-APPLICATION PRECAUTION

LIMITATIONS: COLORCOAT AR is an aromatic topcoat and the surface may become flat and may have some color change over time if exposed to direct sunlight.

PRECAUTION: COLORCOAT AR is a component of the FLEXSTONE Decking Systems. It is primarily used as stipulated in these FLEXSTONE SPECIFICATIONS.

GENERAL: COLORCOAT AR requires a few precautions to be followed during and after application. Each application should be done in one complete step.

MIXING INSTRUCTIONS: Mix COLORCOAT AR thoroughly before using or adding the optional COLORCOAT ACCELERATOR.

APPLICATION: The first coat of COLORCOAT AR should be applied at the rate of 80 to 100 square feet per gallon, depending upon the surface texture.

CURING: Allow COLORCOAT AR to cure at least 24 hours before permitting light pedestrian traffic and at least 72 hours before permitting heavy traffic or placing heavy objects on the completed system.

EQUIPMENT CLEANUP: Equipment should be cleaned immediately with an environmentally-safe solvent, as permitted under local regulations.

TECHNICAL DATA

Table with 4 columns: PhysicalProperty, TestMethod, Results[Metric], Results[English]. Rows include Coverage Rate, Dry Film Thickness per Coat, Hardness, Shelf Life, Specific Gravity, Tear Resistance Die C, Tensile Strength, Total Solids by Weight, Total Solids by Volume, Ultimate Elongation, Viscosity at 24°C (75°F), and Volatile Organic Compounds.

PRECAUTIONS: This product contains flammable solvents. Keep these materials away from heat, sparks and flames. Personnel applying these coatings should wear protective clothing, use respiratory protection, safety goggles and gloves.

LIMITED WARRANTY: Flexstone warrants this product to be free of defects in materials only at the time of shipment from our facility.

This limited warranty is the only warranty extended by FLEXSTONE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose.

The dollar value of FLEXSTONE'S liability and buyer's remedy under his limited warranty shall not exceed the purchase price of the FLEXSTONE material in question.

COLORCOAT AR (07)